

IN THE CLAIMS

The current claims follow. For claims not marked as amended in this response, any difference in the claims below and the previous state of the claims is unintentional and in the nature of a typographical error.

1. (Currently Amended) A wireless communication device comprising:
 - a main controller capable of executing a basic operating system application program that operates communication functions of said wireless communication device and that controls a first graphical user interface (GUI) for interacting with a user;
 - a memory, within the wireless communication device, coupled to said main controller, capable of storing a first GUI configuration file and a second GUI configuration file; wherein said first GUI configuration file contains first GUI parameter data comprising
 - a first plurality of text names~~and~~,
 - a corresponding plurality of data comprising at least one of: sounds, graphical images, text, menu options and a menu hierarchy associated with said first graphical user interface, and
 - a first text name checksum value calculated from only said first plurality of text names, and

said second GUI configuration file contains second GUI parameter data comprising
a second plurality of text names ~~and~~,
a corresponding plurality of data comprising at least one of: sounds, graphical images,
text, menu options and a menu hierarchy associated with a second graphical user interface, and
a first text name checksum value calculated from only said first plurality of text
names; and

wherein said main controller is operable to validate said second GUI parameter data by
comparing [[a]] said first text name checksum value contained in said first GUI configuration file
with [[a]] said second text name checksum value contained in said second GUI configuration file.

2. (Original) The wireless communication device as set forth in Claim 1 wherein said
main controller replaces at least a portion of said first GUI parameter data with said second GUI
parameter data in response to a determination that said first and second text name checksum values
are equal.

3. (Cancelled)

4. (Cancelled)

5. (Original) The wireless communication device as set forth in Claim 2 wherein said first GUI configuration file is a system default GUI configuration file.

6. (Original) The wireless communication device as set forth in Claim 2 wherein said wireless communication device is a cellular telephone handset.

7. (Original) The wireless communication device as set forth in Claim 2 wherein said wireless communication device is a personal digital assistant (PDA) device.

8. (Currently Amended) For use in a wireless communication device comprising a main controller that controls a first graphical user interface (GUI) for interacting with a user, a method of validating data associated with a second graphical user interface comprising the steps of:

retrieving a first text name checksum value stored in a first GUI configuration file in a memory in the wireless communication device, the first GUI configuration file containing first GUI parameter data comprising a first plurality of text names and a corresponding plurality of data comprising at least one of: sounds, graphical images, text, menu options and a menu hierarchy associated with the first graphical user interface, wherein the first text name checksum value is calculated using only the first plurality of text names;

retrieving a second text name checksum value stored in a second GUI configuration file in the memory, the second GUI configuration file containing second GUI parameter data comprising a

second plurality of text names and a corresponding plurality of data comprising at least one of: sounds, graphical images, text, menu options and a menu hierarchy associated with a second graphical user interface, wherein the second text name checksum value is calculated using only the second plurality of text names; and

comparing the first text name checksum value with the second text name checksum value.

9. (Original) The method as set forth in Claim 8 further comprising the step of replacing at least a portion of the first GUI parameter data with the second GUI parameter data in response to a determination that the first and second text name checksum values are equal.

10. (Cancelled)

11. (Cancelled)

12. (Original) The method as set forth in Claim 9 wherein the first GUI configuration file is a system default GUI configuration file.

13. (Original) The method as set forth in Claim 9 wherein the wireless communication device is a cellular telephone handset.

14. (Original) The method as set forth in Claim 9 wherein the wireless communication device is a personal digital assistant (PDA) device.

15. (Previously Presented) A graphical user interface (GUI) configuration file suitable for storing in a memory in a wireless communication device comprising a main controller that controls a graphical user interface (GUI) for interacting with a user, said GUI configuration file containing 1) GUI parameter data comprising a plurality of text names and a corresponding plurality of data comprising at least one of: sounds, graphical images, text, menu options and a menu hierarchy associated with said graphical user interface, and 2) a text name checksum value ~~associated with said GUI configuration file~~ calculated from only said plurality of text names.

16. (Cancelled)

17. (New) The wireless communication device as set forth in Claim 2 wherein said second GUI configuration file is a service provider GUI configuration file.

18. (New) The wireless communication device as set forth in Claim 17 wherein said second GUI configuration file is downloaded to the wireless communication device.

19. (New) The method as set forth in Claim 9 wherein the second GUI configuration file is a service provider GUI configuration file.

20. (New) The method as set forth in Claim 19 wherein said second GUI configuration file is downloaded to the wireless communication device.

21. (New) The GUI configuration file as set forth in Claim 15, wherein the GUI configuration file is a system default GUI configuration file.

22. (New) The GUI configuration file as set forth in Claim 15, wherein the GUI configuration file is a service provider GUI configuration file.